

Elfin I High Resolution Inkjet Printer





5 inch LCD touch screen 5inch 800*480 color LCD touch screen;



Variable Barcode Variable barcode printing supported;







Multi-Functional Port DB15: For external devices like photocell, synchronizer or alarm kit connection;



Vector Font Editor Multi-fonts editing supported;



Smart Detection Smart detection of external devices;



PC-Multiprinters control Remote control by PC software;



Smart Ink Automatical detection of remaining ink volume;

Features

Selectable Languages

Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian;

Fonts

Default font is Arial, allows users to load the fonts they need;

Barcodes

UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, ENA 128, PDF417, DATAMATRIX, QR; (Allows user to add the barcode)

Date format

Variety of date modes available (Production Date, Effective Date, Expiration Date, etc);

Counters

Flexible setting for serial number, Lot-Box code counters;

Print Speed

Print speed can be set, auto-measuring or using external synchronizer;

Multi-Management

Multi-level password protection (Operator, Technician and Administrator);

PC Control

Multiple devices controlled via PC software;

*Date and counters can be switched to variable barcode printing



Technical Parameters

Technology

HP TIJ2.5, utilizing HP driver board for reliability of printing quality;

Dimensions

(H*W*D): 142*65*98mm/ 5.6*2.6*3.9inch;

(Anti-shock cover is not included)

Power Supply

AC 90V-240V/50-60HZ, 60W; (Dedicated AC adaptor)

Printable Heights (mm)

1~12.7mm

Printing speed

0-60 m/min(300 DPI);

Resolution

50~600DPI

Port

1) Ethernet: 100Mb/s, Synchronized control of multiple devices via PC;

- 2) USB2.0: Support U-Disk;
- DB15: For external devices like photocell, synchronizer or alarm kit connection;

Ink Solutions

- 1) Support 42ml, 370ml and 350ml cartridges of HP TIJ2.5 technology;
- 2) Support various colors of ink: black, red, green, blue;
- 3) Support Porous, semi-porous and non-porous materials.

Printing Objects

Barcodes, Character, Numeric, Logos, Date/Time, Expiry Date, Shift Code, Counter, Lot-Box Code;

Interface

- 1) 5inch 800*480 color LCD touch screen;
- 2) 90 degree flip-screen design

Ink management

- Automatically recognize the ink types, and identify the optimum printing parameters;
- 2) Guarantee of using genuine original HP ink;
- 3) Automatic measuring system for the usage of the ink;

Mounting

Standard side, downside and anti-shock printing bracket;

Product Certification

CE、FCC;

Environment

- 1) Working Environment: -10°-- +55°C; 10%-85%RH;
- 2) Storage Environment: -25°-- +80°C; 10%-90%RH;